SPECIFICATION

MICROCEMENT IN THE BATHROOM

Supply of the microcement coating Creativo Microcemento for application on the bathroom floor and walls with ceramic tiles or other existing coatings. Available in more than 1000 colours with glossy, satin or matt finis. Microcement and resin system with a maximum thichkness of 2-3 mm, with CE-marking as per UNI EN 13813 standard, HACCP certified for use in food environments, R9 for anti-slip properties (DIN 51130), abrasion resistance AR 0.5 (UNI EN 13892-4), low water-absorption coefficient W3 (UNI EN 1062-3:2012) and medium vapour-permeability V2 (UNI EN ISO 7783:2012). Creativo Microcement can be applied on tiles and/or other horizontal and vertical surfaces by following the instructions for surface preparation and application provided by the manufacturer in the relative technical data sheet and application manual. It is possible to apply Creativo Microcement in the shower including the shower floor, always following the instructions provided by the manufacturer.

CREATIVO® is a brand of COLORIFICIO MP s.r.l.
Via G. Pastore, 2 Viserba - 47922 Rimini (RN) Italy
Tel +39 0541 734086 | e-mail mp@mp-paints.com
www.creativo-microcement.com

CREATIVO®
NEW SURFACE DESIGN

SPECIFICATION

MICROCEMENT ON FLOORS

Supply of microcement coating Creativo Microcement for application on a pre-existing floor or on new screed, available in more than 1000 colours with glossy, satin or matt finish. Microcement and resin system with a maximum thickness of 2-3 mm, with CE-marking as per UNI EN 13813 standard, HACCP certified for use in food environments, R9 for anti-slip properties (DIN 51130), compressive strength C25 (UNI EN 13892-2), flexural strength F7 (UNI EN 13892-2) and abrasion resistance AR 0.5 (UNI EN 13892-4). The system is classified Bfl-s1 for fire reaction as per UNI EN 13501-1:2009. Creativo Microcement can be applied on new or existing cement-screed, ceramic tiles and other floor coatings, following the instructions provided by the manufacturer in the relative technical data sheet and application manual. The application should be carried out by trained and experienced applicators, following the indications for surface preparation and application of the manufacturer. Creativo Microcement cannot be applied on parquet floor or on vinyl floor.

CREATIVO® is a brand of COLORIFICIO MP s.r.l.
Via G. Pastore, 2 Viserba - 47922 Rimini (RN) Italy
Tel +39 0541 734086 | e-mail mp@mp-paints.com
www.creativo-microcement.com

SPECIFICATION

MICROCEMENT ON THE SCREED

Supply of the microcement coating Creativo Microcemento for application on new or pre-existing cement screed, available in more than 1000 colours with glossy, satin or matt finish. Microcement and resin system with a maximum thickness of 2-3 mm, with CE-marking as per UNI EN 13813 standard, HACCP certified for use in food environments, R9 for anti-slip properties (DIN 51130), compressive strength C25 (UNI EN 13892-2), flexural strength F7 (UNI EN 13892-2) and abrasion resistance AR 0.5 (UNI EN 13892-4). The system is classified Bfl-s1 for fire reaction as per UNI EN 13501-1:2009
The application shall be carried out following the instruction on surface preparation and application provided by the manufacturer in the technical data sheet and application manual of the system. The application shall be carried out by trained and experienced applicators.

CREATIVO® is a brand of COLORIFICIO MP s.r.l.
Via G. Pastore, 2 Viserba - 47922 Rimini (RN) Italy
Tel +39 0541 734086 | e-mail mp@mp-paints.com
www.creativo-microcement.com

SPECIFICATION

MICROCEMENT ON CERAMIC TILES

Supply of microcement coating Creativo Microcemento for application on ceramic tiles and other similar coatings, available in more than 1000 colours with glossy, satin or matt finish. Microcement and resin system with a maximum thickness of 2-3 mm, with CE-marking as per UNI EN 13813 standard, HACCP certified for use in food environments, R9 for anti-slip properties (DIN 51130), compressive strength C25 (UNI EN 13892-2), flexural strength F7 (UNI EN 13892-2) and abrasion resistance AR 0.5 (UNI EN 13892-4). The system is classified Bfl-s1 for fire reaction as per UNI EN 13501-1:2009. Creativo Microcement can be applied over ceramic tiles or similar coatings both on horizontal and vertical surfaces, following the instructions for surface preparation and installation provided by the manufacturer in the relative technical data sheet and application manual. The application should be carried out by trained and experienced applicators.

CREATIVO® is a brand of COLORIFICIO MP s.r.l.
Via G. Pastore, 2 Viserba - 47922 Rimini (RN) Italy
Tel +39 0541 734086 | e-mail mp@mp-paints.com
www.creativo-microcement.com

SPECIFICATION

MICROCEMENT ON WALLS

Supply of microcement coating Creativo Microcement for application on walls with ceramic tiles, plaster, plasterboard, previously painted surfaces, available in more than 1000 colours with glossy, satin or matt finish. HACCP-certified microcement system suitable for application in hospitals and food-processing environments, A+ classified for indoor emissions (EN ISO 16000), water-resistant (Class W3 as per UNI EN 1062-3:2008) and with medium permeability to water vapour (Class V2 as per UNI EN ISO 7783:2012).
Creativo Microcement can be applied directly on ceramic tiles and other pre-existing coatings, plastered walls, old paint, etc. following the instructions for surface preparation and application provided by the manufacturer in the relative technical data sheet and application manual.

CREATIVO® is a brand of COLORIFICIO MP s.r.l.
Via G. Pastore, 2 Viserba - 47922 Rimini (RN) Italy
Tel +39 0541 734086 | e-mail mp@mp-paints.com
www.creativo-microcement.com

SPECIFICATION

MICROCEMENT SHOWER FLOOR

Supply of microcement coating Creativo Microcement for application in the shower and on shower floors, available in more than 1000 colours, with glossy, satin or matt finis. Microcement and resin system with a maximum thickness of 2-3 mm, with CE-marking as per UNI EN 13813 standard, HACCP certified for use in food environments, R9 for anti-slip properties (DIN 51130). For application in the shower the system has a low water-absorption coefficient W3 (UNI EN 1062-3:2012) and medium vapour-permeability V2 (UNI EN ISO 7783:2012). The application of Creativo Microcement in the shower and on the shower floor shall be carried out following the instructions for surface preparation and application provided by the manufacturer in the relative technical data sheet and application manual. It is possible to apply Creativo Microcement in the shower including the shower floor, always following the instructions provided by the manufacturer. The application of the protective PU topcoat Creativo Top should be carried out in 3 coats of which the last two with double catalysis. The application shall be carried out only by trained and experienced applicators.

CREATIVO® is a brand of COLORIFICIO MP s.r.l.
Via G. Pastore, 2 Viserba - 47922 Rimini (RN) Italy
Tel +39 0541 734086 | e-mail mp@mp-paints.com
www.creativo-microcement.com

SPECIFICATION

MICROCEMENT STAIRS

Supply of microcement coating Creativo Microcement for application on cement stairs or stairs with other pre-existing coatings, available in more than 1000 colours with glossy, satin or matt finish. Microcement and resin system with a maximum thickness of 2-3 mm, with CE-marking as per UNI EN 13813 standard, HACCP certified for use in food environments, R9 for anti-slip properties (DIN 51130), compressive strength C25 (UNI EN 13892-2), flexural strength F7 (UNI EN 13892-2) and abrasion resistance AR 0.5 (UNI EN 13892-4). The system is classified Bfl-s1 for fire reaction as per UNI EN 13501-1:2009. Creativo Microcement can be applied on new or existing cement-screed, ceramic tiles and other floor coatings. The application on stairs should be carried out following the instructions provided by the manufacturer in the relative technical data sheet and application manual. The application should be carried out by trained and experienced applicators.

CREATIVO® is a brand of COLORIFICIO MP s.r.l.
Via G. Pastore, 2 Viserba - 47922 Rimini (RN) Italy
Tel +39 0541 734086 | e-mail mp@mp-paints.com
www.creativo-microcement.com