GIORGIO GRAESAN and Friends	TECHNICAL SHEET CERA METALLIZZATA	Code	TDS1011_00
		Revision	00
		Date	22/08/2022

1. DESCRIPTION

CERA METALLIZZATA, formulated with highly biodegradable active ingredients, is a self-polishing polyacrylic metallic wax.

Applied on IPER RESINA, it forms a very hard, non-slip and shiny film, resistant to black marks and pedestrian traffic.

2. USE

On floors treated with IPER RESINA.

3. PREPARING THE SUBSTRATE

The floor treated with IPER RESINA must be cleaned and degreased.

In the case of surfaces already treated with CERA METALLIZZATA, treat with a wax remover and wait for it to dry completely.

4. METHOD OF APPLICATION

Ready to use product, spread CERA METALLIZZATA on IPER RESINA, 7 days after its application and after washing thoroughly with neutral detergent.

Spread CERA METALLIZZATA with tongs and a sausage cloth or wax spreader, taking care to distribute the product evenly without leaving excess and proceeding with small surfaces at a time.

Leave to dry for 30 minutes at 20°C and apply a second or more coats if necessary.

5. CLEANING THE TOOLS

Tools should be cleaned immediately after use with water.

6. CLEANING THE FINISHED PRODUCT

Wash with normal neutral detergent.

7. SAFETY RECOMMENDATIONS AND RISK IDENTIFICATION

The product does not require labelling according to current regulations. Use the product according to current health and safety regulations; after use, do not dispose of containers to the environment; let residue dry thoroughly and handle as special waste. Keep out of the reach of children. If swallowed, seek medical advice immediately and show this container or label. Do not empty into drains, waterways or soil. For more information, see safety data sheet available on: **www.giorgiograesan.it**

TECHNICAL CHARACTERISTICS: APPLICATION	
Dilution	Product is ready for use
Mixing	Always mix before use
Colouring	Not provided
Tools	Tongs and sausage cloth or wax spreader
Primer	Not provided
Conditions of application	From +10°C to +35°C with relative humidity < 85%
Number of coats	1 or more depending on your needs
Drying time	30 minutes at 20°C
Protection	Not provided
Washability	Neutral detergent

TECHNICAL CHARACTERISTICS: COVERAGE	
CERA METALLIZZATA	0.020 litre/m² indicative value

TECHNICAL CHARACTERISTICS: PRODUCT	
Composition	High pressure emulsified polypropylene waxes
Specific weight	1.04 ± 0.02 kg/litre
pH	8.6 ± 1.0
VOC	Paint product not subject to VOC classification
Storage conditions	Keep in tightly sealed container, in a cool, dry place at temperatures between +10°C and +30°C
Packaging	0.5 litres

FOR PROFESSIONAL USE ONLY

Giorgio Graesan & Friends guarantees that the information in this sheet is provided to the best of its experience and its technical and scientific knowledge, however cannot assume any responsibility for the results obtained with their use as the conditions of application are beyond its control. We recommend always checking the actual suitability of the product for each specific case. This sheet nullifies and replaces any previous version.

For more information, call phone number **(+39) 02.9903951** or on **Whatsapp: (+39) 3371410335**.